

CODICE/ CODE	ALIMENTAZIONE/ SUPPLY	RELE/ RELAYS	OUT 1	OUT 2	ING.SONDA/ PROBE INPUT	BUZZER	REM. DISPL.
SCL200L-AA000	12-24VAC-DC	1	8A		PTC/NTC	◆	
SCL200L-AA100	12-24VAC-DC	1	16A		PTC/NTC	◆	
SCL200L-A4000	12-24VAC-DC	1	8A		PT1000	◆	
SCL200L-A4100	12-24VAC-DC	1	16A		PT1000	◆	
SCL200L-A6000	12-24VAC-DC	1	8A		H-NTC	◆	
SCL200L-A6100	12-24VAC-DC	1	16A		H-NTC	◆	
SCL200L-BA000	12VAC-DC	1	8A		PTC/NTC	◆	
SCL200L-BA100	12VAC-DC	1	16A		PTC/NTC	◆	
SCL200L-B4000	12VAC-DC	1	8A		PT1000	◆	
SCL200L-B4100	12VAC-DC	1	16A		PT1000	◆	
SCL200L-B6000	12VAC-DC	1	8A		H-NTC	◆	
SCL200L-B6100	12VAC-DC	1	16A		H-NTC	◆	
SCL200L-EA000	230VAC	1	8A		PTC/NTC	◆	
SCL200L-EA100	230VAC	1	16A		PTC/NTC	◆	
SCL200L-E4000	230VAC	1	8A		PT1000	◆	
SCL200L-E4100	230VAC	1	16A		PT1000	◆	
SCL200L-E6000	230VAC	1	8A		H-NTC	◆	
SCL200L-E6100	230VAC	1	16A		H-NTC	◆	
SCL200L-GA000	12VAC-DC/230VAC	1	8A		PTC/NTC	◆	
SCL200L-GA100	12VAC-DC/230VAC	1	16A		PTC/NTC	◆	
SCL200L-G4000	12VAC-DC/230VAC	1	8A		PT1000	◆	
SCL200L-G4100	12VAC-DC/230VAC	1	16A		PT1000	◆	
SCL200L-G6000	12VAC-DC/230VAC	1	8A		H-NTC	◆	
SCL200L-G6100	12VAC-DC/230VAC	1	16A		H-NTC	◆	
SCL202L-AA000	12-24VAC-DC	2	8A	8A	PTC/NTC	◆	
SCL202L-A4000	12-24VAC-DC	2	8A	8A	PT1000	◆	
SCL202L-A6000	12-24VAC-DC	2	8A	8A	H-NTC	◆	
SCL202L-BA000	12VAC-DC	2	8A	8A	PTC/NTC	◆	
SCL202L-B4000	12VAC-DC	2	8A	8A	PT1000	◆	
SCL202L-B6000	12VAC-DC	2	8A	8A	H-NTC	◆	
SCL202L-EA000	230VAC	2	8A	8A	PTC/NTC	◆	
SCL202L-E4000	230VAC	2	8A	8A	PT1000	◆	
SCL202L-E6000	230VAC	2	8A	8A	H-NTC	◆	
SCL202L-GA000	12VAC-DC/230VAC	2	8A	8A	PTC/NTC	◆	
SCL202L-G4000	12VAC-DC/230VAC	2	8A	8A	PT1000	◆	
SCL202L-G6000	12VAC-DC/230VAC	2	8A	8A	H-NTC	◆	
SCL204L-A2000	12-24VAC-DC	2	8A	8A	NTC	◆	
SCL204L-B2000	12VAC-DC	2	8A	8A	NTC	◆	
SCL204L-E2000	230VAC	2	8A	8A	NTC	◆	
SCL204L-G2000	12VAC-DC/230VAC	2	8A	8A	NTC	◆	
SCL206L-AA000	12-24VAC-DC	2	8A	8A	PTC/NTC	◆	
SCL206L-BA000	12VAC-DC	2	8A	8A	PTC/NTC	◆	
SCL206L-EA000	230VAC	2	8A	8A	PTC/NTC	◆	
SCL206L-GA000	12VAC-DC/230VAC	2	8A	8A	PTC/NTC	◆	
SCL206L-EA020	230VAC	2	8A	8A	PTC/NTC	◆	X

Tutti i modelli 32x74 sono disponibili anche in formato 4 DIN. / All the 32x74 models are also available in 4DIN case.

X = Standard/Standard ◆ = Opzionale/Optional

CARATTERISTICHE COMUNI / COMMON FEATURES

(*) Valore dipendente da modello / Value depending on model

Campo di lavoro/Operation field (*):	Sonda NTC: -40...120°C Sonda PTC: -50...150°C Sonda H-NTC: 0...300°C Sonda PT1000: -50...200°C	NTC: -40...120°C PTC: -50...150°C H-NTC: -100...800°C PT1000: -50...200°C
Contenitore/Housing:	32x74 plastico: 75 x 33 x 63 (74)mm DIN RAIL plastico: DIN 4 moduli	32x74 in plastic: 75 x 33 x 63 (74)mm DIN RAIL in plastic: DIN 4 modules
Montaggio/Assembling:	32x74: a pannello su foro 71 x 29mm DIN: guida OMEGA	32x74: on panel, hole 71 x 29mm DIN: OMEGA rail
Mantenimento dati/Data maintenance:	su memoria EEPROM	on EEPROM memory
Protezione frontale/Front protection:	32X74: IP65 / DIN: IP00	32X74: IP65 / DIN: IP00
Condizioni di utilizzo/Employment conditions:	temperatura ambiente: -10...50°C temperatura di immagazzinamento: -20...70°C	environment temperature: -10...50°C storage temperature: -20...70°C
Umidità relativa ambiente/Relative environm. humidity:	30 / 80% senza condensa	30 / 80% , no condensing
Connessioni/Connections (*):	morsetti a vite per fili Ø max di 2,5mmq o mors. estraibili per blocchetti a vite o a crimpare.	screw-terminals for cables with 2,5 sqmm max Ø or plug-in terminal for screw or clamp connectors.